


| 精度等级/General Tolerances(mm) | |
|-----------------------------|-------|
| 0 | >3 |
| ~ | >6 |
| 3 | 10 |
| 6 | 18 |
| ~ | 30 |
| ±0.12 | ±0.18 |
| ±0.22 | ±0.26 |
| ±0.31 | ±0.37 |
| ±0.57 | ±0.80 |
| ±0.93 | ±1.05 |
| ±1.15 | ±1.60 |
| ±2.20 | ±2.50 |
| ±Z | ±Z |



| ITEM | NAME OF PART | MATERIAL | NOTES |
|------|--------------|-----------------|-----------|
| 1 | Housing 1 | PA66 | UL94V-0 |
| 2 | Side Housing | PA66 | UL94V-0 |
| 3 | Cover 1 | PA66 | UL94V-0 |
| 4 | Cover 2 | PA66 | UL94V-0 |
| 5 | Pin | Copper | Sn Plated |
| 6 | Spring | Stainless Steel | |
| 7 | Housing 2 | PA66 | UL94V-0 |

| UL 标准/UL Standard: | B | C | D |
|--|---------------|--------|--------|
| 额定电压/Rated Voltage(V)/Current(A) | 300/15 | / | 300/10 |
| IEC 标准/IEC Standard: | | | |
| 过压类别/Overvoltage Category/污染等级 | III/3 | III/2 | II/2 |
| 绝缘/Insulation Degree | / | 320/20 | / |
| 额定电压/电涌/Rated Voltage(V)/Current(A) | / | / | 4 |
| 额定电涌电压(kV)/Rate Impulse Voltage(kV) | 0.2~2.5/22~14 | | |
| 线芯范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG) | 5.08/N=02~24P | | |
| 间距/Pitch(mm)/线芯范围/Poles | 9-10 | | |
| 剥线长度/Stripping length(mm) | -40~+105 | | |
| 使用温度范围/Operating temperature(°C) | Yes | | |
| 符合RoHS环保要求/Conform to RoHS | | | |
| 标准颜色编号/Standard color number: | PANTONE 7534u | | |

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
宁波高松电子有限公司

CHKD: /
 DFT: CenX 2020.06.15
 DRAWING NO.: 8EDGKRMA-5.08-C02
 TYPE: CUSTOMER DRAWING
 SCALE: 2:1
 SHEET 1/1

| REV | ECN | DESCRIPTION | DFT | DATE |
|-----|-----|-------------|-----|------|
| | | | | |

D C B A

1 2 3 4 5 6