



公差等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>280	>315	>400	>500	0.1/1.0
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±Z	±Z

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 1:1	REV	T0

  

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/	DRAWING NO.: 10001975	
APPD:	LanChH 2020.05.20	NAME: DG137T-15.0-XXP-1Y-00A(H)	
CHKD:	YUZh 2020.05.20	DRAWING NO.: 10001975	
DRAFT:	BqYH 2020.05.20	TYPE: CUSTOMER DRAWING	

ITEM	NAME OF PART	MATERIAL	NOTES
4	Screw	Steel	M5/Zn Plated
3	Cage	Steel	M5/Zn Plated
2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0

  

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/115	600/115	600/115
IEC 标准/IEC Standard:	/		
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/2		
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/115		
工频耐压/Withstanding voltage(V/1min)	AC3500		
螺栓扭矩/Torque Tightening(N·m/Lb·in)	M5: 2.0/17.54		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	4~35/20~2		
间距/Pitch(mm)/线数范围/Poles	15.00/N=2~9P		
剥线长度/Stripping length(mm)	18~19		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		