



公差范围 (General Tolerances)(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
~	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±0.93	±1.05
±1.15	±1.60
±2.20	±2.50
0.1/1.0	±2

4	Nut	Copper alloy	/
3	Pin	Copper	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:			
		B	C
			D
额定电压/电流/Rated Voltage(V)/Current(A)			
		300/15	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级			
		III/3	III/2
级/ Pollution Degree			
		/	320/10
额定电压/电流/Rated Voltage(V)/Current(A)			
		/	4
额定脉冲电压/Rate Impulse Voltage(KV)			
			N=0.4~48P
使用温度范围/Operating Temperature(°C)			
			-40~+105
符合RoHS环保要求/Conform to RoHS			
			Yes

MATERIAL: SURFACE: Yes

MAT NO.: /

STATUS: /

APPD: Lon CHH 2020.05.23

CHKD: /

DRT: Both 2018.09.30

DRAWING NO.: ZEDGVHM-5.0-C01

TYPE: CUSTOMER DRAWING

SCALE: 1:1 SHEET 1/1

NAME: 宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD

2EDGVHM-5.0-XXP-1Y-00A(H)

REV	ECN	DESCRIPTION	DRT	DATE
1				