



精度等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	
3	6	10	18	30	50	80	120	180	250	315	400	500	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50	

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing1	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
3	Screw	Steel	Zn plated
4	Current Carrier	Copper	Sn plated
5	Groupware	PA66	UL94V-0
6	Sliding part 1	PA66	UL94V-0
7	Sliding part 2	PA66	UL94V-0
8	Spring	Spring Steel	Ni plated

REV	ECN	DESCRIPTION	DRAFT	DATE
1				

MATERIAL: /	SURFACE: /
MAT NO.: /	
STATUS: /	
APPD: Li GL 2020.05.30	NAME: DEGSON 宁波高松电子有限公司
CHKD: Mco J 2020.05.30	NINGBO DEGSON ELECTRICAL CO., LTD
DRAFT: ZhengQG 2020.05.16	DRAWING NO.: PC95-C02
	TYPE: CUSTOMER DRAWING
	SCALE: 1:1.5 SHEET
	REV T2
	1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/230	/	/
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/232	/	/
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	8	/	/
额定扭矩/螺栓和线材/Torque Tightening(N·m/Lb·in)	M8: 20/177		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	25~95/2~4/0		
间距/Pitch(mm)	25.0		
剥线长度/Stripping length(mm)	33~35		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS标准/Conform to RoHS	Yes		