



Pitch range in mm	Nominal dimension range					
	In mm		In mm			
6	over 10	over 30	over 60	over 100	over 150	□
to 10	to 10	to 30	to 60	to 100	to 150	
to 15	to 24	to 60	to 100	to 150		
HD: 10	HD: 15	HD: 25	HD: 25±0.2	HD: 35±0.3	HD: 50±0.7	HD: 1.0±0.05/0.10

3	Screw	Steel	Ni Plated
2	Pin header	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL Standard: B C D			
额定电压/电流/Rated Voltage(V)/Current(A)		300/25	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/ Pollution Degree		III/3	III/2
额定电压/电流/Rated Voltage(V)/Current(A)		500/32	600/32
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		6	6
螺丝扭矩/Torque Tightening(N·m/Lb·in)		M4, 1.2/10.53	6
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)		0.34~4/22~12	
间距/Pitch(mm)/线数范围/Poles		9.50/N=02~24P	8
剥线长度/Stripping length(mm)			8
使用温度范围/Operating temperature(°C)			-40~+105
符合RoHS环保要求/Conform to RoHS			Yes

SURFACE: /

MATERIAL: /
 MAT NO.: /
 STATUS: work
 APPD: /
 CHKD: /

NAME: **DEGSON** 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: DG45C-C03

TYPE: CUSTOMER DRAWING

SCALE: 3:2

REV	ECN	DESCRIPTION	DRFT	DATE