



ITEM	NAME OF PART	MATERIAL	NOTES
6	Calpboard	PA66	UL94V-0
5	Spring	Stainless steel	/
4	Pin header	Copper alloy	Sn Plated
3	Button	PA66	UL91V-0
2	Cover	PA66	UL91V-0
1	Housing	PA66	UL91V-0

REV	ECN	DESCRIPTION	DRAFT	DATE

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/	NAME: DG235-7.5-XXP-1Y-00A(H)	
APPD: LiGL	202.05.28	DRAWING NO.:	DG235-7.5-C01
CHKD: Mek	2020.05.28	TYPE:	CUSTOMER DRAWING
DRAFT: MSh	2020.05.28	SCALE:	2.5:1 SHEET 1/1

UL 标准 / UL Standard:	B	C	D
额定电压/电涌 / Rated Voltage(V)/Current(A)	300/5	150/5	300/5
EC 标准 / EC Standard:	III/3	III/2	II/2
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压/电涌 / Rated Voltage(V)/Current(A)	400/17.5	1000/17.5	1000/17.5
额定电压/电涌 / Rated Voltage(V)/Rate Impulse Voltage(KV)	8	8	8
线径范围(硬线和软线) / Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~1.5	2.5(Sol)	20~18
间距 / Pitch(mm) / 线径范围 / Poles	7.5	N=02~16P	
剥线长度 / Stripping length(mm)	10		
使用温度范围 / Operating temperature(°C)	-40~+105		
符合 RoHS 要求 / Conform to RoHS	Yes		
标准颜色编号 / Standard color number:	/		
PANTONE / RAL	/		