

Áttekintés

Termék információ



Interface module-DM50-IDC-34-40-4M-00A(H)-30040000093

Mitsubishi PLC dedicated, with indicator light, with screw connector and IDC stitching line, can be installed on DIN35 rail, 40 positions

A termék előnyei

The signal is clearly marked and the wiring is simple
Screw connection

Termék tanúsítás

Műszaki adatok

Termékrajz

3D modell

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
-----------------------	-----------

Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	32
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	34
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	111mm
width	57mm
Height	44mm

Melléklet	
Accessories	
Wire harness	DX210-4S-500-00A(H)

Üzleti adatok	
Rendelészám	30040000093
Csomagolási egység	1
Minimális rendelési mennyiség	10
A termékek súlya (csomagolás nélkül)	128