

Áttekintés

Termék információ



Interface module-DM50-DG-8-10-1N-00A(H)-30040000012

8 positions output module, I/O interface module, can access binary or ternary NPN signal, with indicator light, with screw connector, can be installed on DIN35 rail

A termék előnyei

Quick-plug wiring
Screw connection
Can be connected to 2 or 3 NPN signals
With indicator light

Termék tanúsítás

Műszaki adatok

Termékrajz

3D modell

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
---------------------------------	------------------

Ambient temperature (storage / transport)	-20 °C ... 70 °C
---	------------------

Standards/Regulations

Standards/Regulations	IEC61810
-----------------------	----------

Pollution level	3
-----------------	---

Overvoltage category	III
----------------------	-----

Rated overvoltage	0.5kV
-------------------	-------

Flame retardant grade, in line with UL94	V0
--	----

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	2A
Signal points	8
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	Screw connection
Connection volume	1
Number of digits	10
spacing	5.08mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	0.5mm² ... 1.5 mm²
Connectable guide cross section AWG	28-16AWG
Connection meets standards	UL1059
Connection method	Plug screw connection
Connection volume	8
Number of digits	3
screw thread	M2
Hard wire cross section	0.5mm² ... 1.5 mm²

Dimension

length	65.5mm
width	57mm

Height	35mm
--------	------

Melléklet

Üzleti adatok	
Rendelészám	30040000012
Csomagolási egység	2
Minimális rendelési mennyiség	10
A termékek súlya (csomagolás nélkül)	76