


## Áttekintés

## Termék információ

**DK-4/2-F-21020000062**

Heavy-duty insert, Number of contacts: 4/2+PE, Dimension: 16B, Rated voltage : 690/400V, Rated current: 80/16A, Female insert, Screw connector

## A termék előnyei

- ☒ Screw connection technology, applicable to a wide range of wire specifications;
- ☒ No need special tools, easy to operate;
- ☒ Less materials, easy to manage;
- ☒ With grounding protection.

## Termék tanúsítás



## Műszaki adatok

## Termékrajz

## 3D modell



## Marking

classification

Insert

Series

DK

## versions

Connection method

Screw connection

Female/Male

Female

Dimension

16B

Number of positions

4/2

PE Contacts

Yes

Material characteristics

|                     |                             |
|---------------------|-----------------------------|
| Material (insert)   | Polycarbonate (PC)          |
| Materia (Contact)   | Copper alloy                |
| Surface (Contact)   | Silver plated               |
| Flammability rating | V-0                         |
| color               | Grey/White (RAL 7032)       |
| RoHS                | Comply with RoHS exemptions |

Electrical parameters

|                                      |                                                          |
|--------------------------------------|----------------------------------------------------------|
| Rated current                        | 80/16A                                                   |
|                                      | 690/400V                                                 |
| Rated pulse voltage                  | 8/6KV                                                    |
| Pollution level                      | 3                                                        |
| On the basis of UL /CSARated current | 600/300V                                                 |
| Insulation resistance                | ≥10000MΩ                                                 |
| Contact resistance                   | ≤0.3mΩ                                                   |
| Temperature range                    | -40℃~+125℃                                               |
| working life-mating cycles           | ≥500 time                                                |
| Strip length                         | 14/7.5mm                                                 |
| Rated torque                         | 1.2N.m(1.5mm²) 2N.m(2.5mm²) 3N.m(4/6/10/16mm²)<br>0.5N.m |
| Conductor cross sections (mm²)       | 1.5-16mm²                                                |
| Conductor cross sections(AWG)        | 16-6AWG                                                  |

Standards

|                            |                           |
|----------------------------|---------------------------|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |
|----------------------------|---------------------------|

Accessories

|             |   |
|-------------|---|
| Screwdriver | / |
|-------------|---|

Üzleti adatok

|                                      |             |
|--------------------------------------|-------------|
| Rendelészám                          | 21020000062 |
| Csomagolási egység                   | 100         |
| Minimális rendelési mennyiség        | 5           |
| A termékek súlya (csomagolás nélkül) | 116         |