


## Áttekintés

## Termék információ

**DK-8/24-FC-21020000126**

Heavy-duty insert, Number of contacts: 8/24+PE, Dimension: 10B, Rated voltage : 400/160V, Rated current: 16/10A, Female insert, Crimping connector

## A termék előnyei

- ☒ Crimping connection technology, high wiring efficiency
- ☒ Suitable for vibration occasions;
- ☒ The wiring harness can be pre-installed;
- ☒ Choose contacts with different wire diameters and coatings;
- ☒ High-density pins, saving installation space;
- ☒ With grounding protection.

## Termék tanúsítás



## Műszaki adatok

## Termékrajz

## 3D modell



## Marking

|                |        |
|----------------|--------|
| classification | Insert |
| Series         | DK     |

## versions

|                     |                     |
|---------------------|---------------------|
| Connection method   | Crimping connection |
| Female/Male         | Female              |
| Dimension           | 10B                 |
| Number of positions | 8/24                |

|             |     |
|-------------|-----|
| PE Contacts | Yes |
|-------------|-----|

Material characteristics

|                     |                             |
|---------------------|-----------------------------|
| Material（insert）    | Polycarbonate（PC）           |
| Materia（Contact）    | Copper alloy                |
| Surface（Contact）    | Silver plated/gold plated   |
| Flammability rating | V-0                         |
| color               | Grey/White（RAL 7032）        |
| RoHS                | Comply with RoHS exemptions |

Electrical parameters

|                                      |                         |
|--------------------------------------|-------------------------|
| Rated current                        | 16/10A                  |
|                                      | 400/160V                |
| Rated pulse voltage                  | 6/4KV                   |
| Pollution level                      | 3                       |
| On the basis of UL /CSARated current | 600/300V                |
| Insulation resistance                | ≥10000MΩ                |
| Contact resistance                   | ≤1/3mΩ                  |
| Temperature range                    | -40℃~+125℃              |
| working life-mating cycles           | ≥500 time               |
| Strip length                         | 6-8mm                   |
| Conductor cross sections（mm²）        | 0.5-4.0mm² /0.14-2.5mm² |
| Conductor cross sections(AWG)        | 20-12/26-12AWG          |

Standards

|                            |                           |
|----------------------------|---------------------------|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |
|----------------------------|---------------------------|

Accessories

|                            |   |
|----------------------------|---|
| Crimping tool Removal tool | / |
|----------------------------|---|

Üzleti adatok

|                                      |             |
|--------------------------------------|-------------|
| Rendelészám                          | 21020000126 |
| Csomagolási egység                   | 100         |
| Minimális rendelési mennyiség        | 5           |
| A termékek súlya (csomagolás nélkül) | 53          |