


Áttekintés

Termék információ



DE-010-M-21020000030

Heavy-duty insert, Number of contacts: 10+PE, Dimension: 10B, Rated voltage :500V, Rated current: 16A, Male insert, Screw connector

A termék előnyei

- ☒ Screw connection technology, applicable to a wide range of wire specifications;
- ☒ No need special tools, easy to operate;
- ☒ Less materials, easy to manage;
- ☒ With grounding protection.

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Marking

classification	Insert
Series	DE

versions

Connection method	Screw connection
Female/Male	Male
Dimension	10B
Number of positions	10
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	500V
Rated pulse voltage	6KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7mm
Rated torque	0.5N.m
Conductor cross sections (mm²)	0.75-2.5mm²
Conductor cross sections(AWG)	18-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Melléklet

Accessories

Screwdriver

/

Üzleti adatok

Rendelészám	21020000030
Csomagolási egység	100
Minimális rendelési mennyiség	5
A termékek súlya (csomagolás nélkül)	68.3