


Áttekintés

Termék információ

**DDD-216-FC-21020000194**

Heavy-duty insert, Number of contacts: 216+PE, Dimension: 48B, Rated voltage : 250V, Rated current: 10A, Female insert, Crimping connector

A termék előnyei

- ☒ Crimping connection technology, high wiring efficiency
- ☒ Suitable for vibration occasions;
- ☒ The wiring harness can be pre-installed;
- ☒ Choose contacts with different wire diameters and coatings;
- ☒ High-density pins, saving installation space;
- ☒ With grounding protection.

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

☐

Marking

classification

Insert

Series

DDD

versions

Connection method

Crimping connection

Female/Male

Female

Dimension

48B

Number of positions

216

PE Contacts	Yes
-------------	-----

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	250V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	6-8mm
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessories

Crimping tool Removal tool	/
----------------------------	---

Üzleti adatok

Rendelészám	21020000194
Csomagolási egység	100
Minimális rendelési mennyiség	5
A termékek súlya (csomagolás nélkül)	158