

Áttekintés

Termék információ

**DA-003-M-21020000002**

Heavy-duty insert, Number of contacts: 3+PE, Dimension: 3A, Rated voltage: 400/230V, Rated current: 10A, Male insert, Screw connector

A termék előnyei

- ✓ Screw connection technology, applicable to a wide range of wire specifications;
- ✓ No need special tools, easy to operate;
- ✓ Less materials, easy to manage;
- ✓ With grounding protection.

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Marking

classification

Insert

Series

DA

versions

Connection method

Screw connection

Female/Male

Male

Dimension

3A

Number of positions

3

PE Contacts

Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	400/230V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	4.5mm
Rated torque	0.25N.m
Conductor cross sections (mm²)	0.75-1.5mm²
Conductor cross sections(AWG)	18-16AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Melléklet

Accessories

Screwdriver

/

Üzleti adatok

Rendelészám	2102000002
Csomagolási egység	100
Minimális rendelési mennyiség	5
A termékek súlya (csomagolás nélkül)	13.65