

Áttekintés

Termék információ

**FT-M12D-04F-M12D-04M-K4-0200-20030002032**

M12D-T distributor(soldering), Input terminal: Female, Output terminal1: Male, Output terminal2: Female

A termék előnyei

- ☒ Single wire input, Multi wire output
- ☒ Cost saving and convenient installation
- ☒ Protection level: IP67/68
- ☒ Widely used in industrial automation, rail transit and other industries

Termék tanúsítás

RoHS REACH

Műszaki adatok

Termékrajz

3D modell

□

Environmental conditions

Ambient temperature

-25°C...85°C

IP class

IP67

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

D-Code

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100

Material

Flammability rating ,in line with UL97	HB
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Melléklet

Üzleti adatok

Rendelészám	20030002032
Csomagolási egység	/
Minimális rendelési mennyiség	100
A termékek súlya (csomagolás nélkül)	/