


Áttekintés

Termék információ



DGR30-10A(H)-12010000263

Transfer barrier terminal blocks, Rated current: 30A. Rated voltage (UL) : 600V, Cross section: 20~10AWG, pitch: 11.5mm, Color: black, Contact surface: Tin

A termék előnyei

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Provide the cabinet and panel electrical transfer connections

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Connection capacity

AWG

20~10AWG

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	30A
Rated current (D)	5A
Rated current (C)	30A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M4
Pitch	11.5mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

Melléklet

Accessories

--	--

Üzeti adatok

Rendelészám	12010000263
Csomagolási egység	54
Minimális rendelési mennyiség	/
A termékek súlya (csomagolás nélkül)	40