

Áttekintés

Termék információ

**TSF2.5-10070000095**

Transformer terminal blocks, Rated current: 6.3A. Rated voltage
(III/2) : 250V, Color: Orange, Contact surface : Tin

A termék előnyei

- ☒ Screw connection technology, safe and reliable
- ☒ Rail installation method, suitable for transformer wiring

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Connection capacity

Conductor cross section solid	0.5~2.5mm ²
Conductor cross section flexible	0.5~2.5mm ²
AWG	20~14AWG
Torque	0.8N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	250V
Rated voltage (C)	250V
Rated voltage (D)	250V

Rated current (B)	6.3A
Rated current (D)	10A
Rated current (C)	6.3A

Electrical parameters IEC

Rated current	250V
	6.3A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3.5
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Melléklet

Accessories

Coding strip	TSZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Üzleti adatok

Rendelészám	10070000095
Csomagolási egység	250
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	9