

Áttekintés

Termék információ

**TSB4-10070000035**

Transformer terminal blocks, Rated current: 32A. Rated voltage
(III/2) : 450V, Color: Orange, Contact surface : Tin

A termék előnyei

- ☒ Screw connection technology, safe and reliable
- ☒ Rail installation method, suitable for transformer wiring

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell



Connection capacity

Conductor cross section solid	0.5~4mm ²
Conductor cross section flexible	0.5~4.0mm ²
AWG	20~12AWG
Torque	1.2N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	30A
Rated current (D)	5A
Rated current (C)	30A

Electrical parameters IEC

Rated current	450V
	32A
Rated current(III/2)	450V
Rated surge voltage(III/2)	3KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M4
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Melléklet

Accessories

Coding strip	TZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Üzleti adatok

Rendelészám	10070000035
Csomagolási egység	100
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	5