


Áttekintés

Termék információ

**DGH50-10090000013**

Through-wall terminal blocks, Rated current: 150A. Rated voltage
(III/2) : 1000V, Width: 18.8mm, Color: gray, Contact surface : Tin

A termék előnyei

- ✓ Screw connection technology, safe and reliable
- ✓ Through-wall installation, free positioning

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell



Connection capacity

Conductor cross section solid	16~50mm ²
Conductor cross section flexible	16~50mm ²
AWG	6~2/0AWG
Strip length	24mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	170A

Rated current (D)	5A
Rated current (C)	170A

Electrical parameters IEC

Rated current(III/3)	690V
Rated current	500V
	150A
Rated current(III/2)	1000V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M6
Pitch	18.8mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated

Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL 1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Melléklet

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Üzleti adatok

Rendelészám	10090000013
Csomagolási egység	20
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	120