


## Áttekintés

### Termék információ



**DGH25-10090000007**

Through-wall terminal blocks, Rated current: 101A. Rated voltage (III/3) : 500V, Width: 15.0mm, Color: gray, Contact surface : Tin

### A termék előnyei

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

### Termék tanúsítás



## Műszaki adatok

### Termékrajz

### 3D modell

□

### Connection capacity

|                                  |                      |
|----------------------------------|----------------------|
| Conductor cross section solid    | 6~35mm <sup>2</sup>  |
| Conductor cross section flexible | 10~25mm <sup>2</sup> |
| AWG                              | 8~2AWG               |
| Torque                           | 4N.m                 |
| Strip length                     | 19mm                 |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 600V |
| Rated voltage (C) | 600V |
| Rated voltage (D) | 600V |

|                   |      |
|-------------------|------|
| Rated current (B) | 115A |
| Rated current (D) | 5A   |
| Rated current (C) | 115A |

#### Electrical parameters IEC

|                            |      |
|----------------------------|------|
| Rated current(III/3)       | 500V |
| Rated current              | 500V |
|                            | 101A |
| Rated surge voltage(III/3) | 6KV  |

#### Item properties

|                      |                     |
|----------------------|---------------------|
| Type of installation | panel               |
| Connection method    | Screw connection    |
| Screwdriver          | Slotted screwdriver |
| screw thread         | M5                  |
| Pitch                | 15.1mm              |
| Number of potentials | 1                   |
| Pluggable or not     | Yes                 |
| Number of rows       | 1                   |

#### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Contact zone metal surface  | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

| Mechanical tests                |                 |
|---------------------------------|-----------------|
| Test Specification              | IEC60947/UL1059 |
| Environmental data              |                 |
| Ambient temperature (operation) | -40°C~105°C     |

| Melléklet      |      |
|----------------|------|
| Accessories    |      |
| Coding strip   | ZB15 |
| Bridge         | /    |
| Marking strip  | /    |
| Others         | /    |
| Tool           |      |
| Operating tool | /    |
| Screwdriver    | /    |

| Üzleti adatok                        |             |
|--------------------------------------|-------------|
| Rendelészám                          | 10090000007 |
| Csomagolási egység                   | 12          |
| Minimális rendelési mennyiség        | 30          |
| A termékek súlya (csomagolás nélkül) | 133         |