

Áttekintés

Termék információ

**DGH16-10090000006**

Through-wall terminal blocks, Rated current: 76A. Rated voltage
(III/2) : 500V, Width: 12.1mm, Color: gray, Contact surface : Tin

A termék előnyei

- ✓ Screw connection technology, safe and reliable
- ✓ Through-wall installation, free positioning

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell



Connection capacity

Conductor cross section solid	0.5~16mm ²
Conductor cross section flexible	0.5~16mm ²
AWG	20~4AWG
Torque	2N.m
Strip length	16mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	85A
Rated current (D)	5A
Rated current (C)	85A

Electrical parameters IEC

Rated current	500V
	76A
Rated current(III/2)	500V
Rated surge voltage(III/2)	6KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M5
Pitch	12.1mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Melléklet	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Üzleti adatok	
Rendelészám	10090000006
Csomagolási egység	25
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	36.8