

Áttekintés

Termék információ

**DG15HS-1.2-10080000058**

Feed through terminal blocks, Rated current: 76A. Rated voltage
(III/2) : 750V, pitch: 15.0mm, Color: natural, Contact surface : Zn

A termék előnyei

- ☒ Can realize horizontal wire-to-wire connection
- ☒ Panel mounting, suitable for various situations

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Connection capacity

Conductor cross section solid	2.5~16mm ²
Conductor cross section flexible	2.5~16mm ²
AWG	12~10AWG
Torque	1.2N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	30A

Rated current (D)	10A
-------------------	-----

Electrical parameters IEC

Rated current	750V
	76A
Rated current(III/2)	750V
Rated power frequency voltage(1min)	3KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	15mm
Number of potentials	12
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Melléklet

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Üzleti adatok

Rendelészám	10080000058
Csomagolási egység	40
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	93.8