

Áttekintés

Termék információ



DG97-A-12050000147

Transfer Type,nominal current60A.Rated voltage(UL): 300V,Rated cross section:22~3AWG,pitch:12mm,Color:black,Contact surface:Tin

A termék előnyei

- ☒Screw connection for worldwide use
- ☒Screw connection for worldwide use
- ☒Provide the cabinet and panel electrical transfer connections

Termék tanúsítás

Műszaki adatok

Termékrajz

3D modell

□

Wiring capacity

torque

3N.m

Connectable conductor cross section

22~3AWG

Device properties

spacing

12mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (C)

300V

Rated voltage (D)

300V

Rated current (B)

60A

Rated current (D)

10A

Rated current (C)	60A
-------------------	-----

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M6
Number of potentials	12
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

Melléklet

Accessories

--	--

Üzleti adatok

Rendelészám	12050000147
Csomagolási egység	8
Minimális rendelési mennyiség	/
A termékek súlya (csomagolás nélkül)	402.7