


Áttekintés

Termék információ

**DGV10-10090000027**

Through-wall terminal blocks, Rated current: 57A, Rated voltage (III/3) : 400V, width: 10.1mm, Color: gray, Contact surface :Tin

A termék előnyei

- ☑ Screw connection technology, safe and reliable
- ☑ Through-wall installation, free positioning

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Connection capacity

Conductor cross section solid	0.5~16mm ²
Conductor cross section flexible	0.5~10mm ²
AWG	24~6AWG
Torque	1.2N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	150V
Rated voltage (D)	300V

Rated current (B)	65A
Rated current (D)	10A
Rated current (C)	65A

Electrical parameters IEC

Rated current(III/3)	400V
Rated current	400V
	57A
Rated surge voltage(III/3)	6KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Melléklet

tool

screwdriver

0.8x4.0mm, Slotted screwdriver

Operating tool

/

Accessories

Coding strip

/

Marking strip

ZB10

Bridge

EB xx-10

Other

/

Accessories

Coding strip

/

Bridge

/

Marking strip

ZB10

Others

/

Tool

Operating tool

/

Screwdriver

1.0x4.0mm, Slotted screwdriver

Üzleti adatok

Rendelészám

10090000027

Csomagolási egység

50

Minimális rendelési
mennyiség

A termékek súlya
(csomagolás nélkül)

21.78