

Áttekintés

Termék információ



DG2350-50A(H)-12010000610

Single-layer PCB barrier terminal blocks, Rated current: 120A. Rated voltage(UL): 600V. Cross section: 2-1/0AWG Pitch: 23.5mm. Color: black, Contact surface: Tin

A termék előnyei

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ High current electrical connections at power end can be met

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Wiring capacity

torque

5.5N.m

Connectable conductor cross section

2~1/0AWG

Device properties

number of digits

23.5mm

Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated voltage (D)

600V

Rated current (B)	120A
Rated current (D)	5A
Rated current (C)	120A

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8
Number of potentials	4
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

Üzleti adatok

Rendelészám	12010000610
Csomagolási egység	20
Minimális rendelési mennyiség	
A termékek súlya (csomagolás nélkül)	195.66