


Áttekintés

Termék információ



DC2.5-QU-PE-11020000215

Screw type Din-Rail TB, connector method: Screw/plug-in connector,
Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm² -
4 mm², AWG: 28 - 12, Width: 5.1 mm, Color: green-yellow, Mounting
type: NS 35/7.5, NS 35/15

A termék előnyei

- ☒ Steel screw connection technology, reliable connection;
- ☒ Grounding structure, protection circuit;
- ☒ The box has a baffle to prevent mis-insertion;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell



Wiring data

Screw type	Cross & Slotted screw
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-1.5mm ²
Strip length	8~9mm
Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~2.5mm ²
Conductor cross section solid AWG	28~12
screw thread	M2.5

Tightening torque	0.4N.m
-------------------	--------

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	6KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	49.2mm
End plate width	1.5mm
NS 35/15 Height	56.7mm
length	54.4mm
width	5.1mm
Height	47.7mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Marker

Top marker	/
Side marker	ZB5 / WB5
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Bridge	DFA2.5
End cover	D-DC4-QU
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Üzleti adatok

Rendelészám	11020000215
Csomagolási egység	100
Minimális rendelési mennyiség	100
A termékek súlya (csomagolás nélkül)	9.73