

## Áttekintés

### Termék információ



## DGBSC-SG02/4-10080000436

Building wiring terminals, Rated current: 32A. Rated voltage (III/2): 450V, max. 4 mm<sup>2</sup>, Color: transparent, Contact surface: Tin

### A termék előnyei

- ☒ Rotatable operating handle, easy to operate
- ☒ Suitable for all conductors types
- ☒ Suitable for field wiring, saving installation time

### Termék tanúsítás

## Műszaki adatok

### Termékrajz

### 3D modell

□

### Connection capacity

|                                  |                        |
|----------------------------------|------------------------|
| Conductor cross section solid    | 0.2~4mm <sup>2</sup>   |
| Conductor cross section flexible | 0.2~4.0mm <sup>2</sup> |
| AWG                              | 24~12AWG               |
| Strip length                     | 12mm                   |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (C) | 600V |
|-------------------|------|

### Electrical parameters IEC

|                      |      |
|----------------------|------|
| Rated voltage        | 450V |
| Rated current        | 32A  |
| Rated current(III/2) | 450V |

|                                     |                           |
|-------------------------------------|---------------------------|
| Rated power frequency voltage(1min) | 2.5KV                     |
| Item properties                     |                           |
| Connection method                   | Push-in spring connection |
| Number of potentials                | 2                         |
| Pluggable or not                    | no                        |
| Number of rows                      | 1                         |
| Material data                       |                           |
| Environmental items                 | Compliant with REACH/RoHS |
| Contact material                    | copper                    |
| Contact point metal surface         | tin-plated                |
| Contact zone metal surface          | tin-plated                |
| Insulation Materials                | PC                        |
| Shell color                         | Transparent               |
| Flammability rating                 | UL94V-2                   |
| Environmental data                  |                           |
| Ambient temperature (operation)     | -40℃~85℃                  |

|           |
|-----------|
| Melléklet |
|           |

|                                      |             |
|--------------------------------------|-------------|
| Üzleti adatok                        |             |
| Rendelészám                          | 10080000436 |
| Csomagolási egység                   | 100         |
| Minimális rendelési mennyiség        |             |
| A termékek súlya (csomagolás nélkül) | 3.22        |

