


Áttekintés

Termék információ



9EDGRB-HC-5.0-10030010262

Pluggable terminal blocks, Rated current: 20A. Rated voltage (III/3) : 300V, pitch: 5.0mm, Color: black, Contact surface : Tin

A termék előnyei

- ☒ Push-in spring connection, easy wiring
- ☒ SNAP-LOCK series, with self-locking buckle

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Packaging information

Type of packaging

box-packed

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

20A

Rated current (D)

10A

Electrical parameters IEC

Rated voltage

300V

Rated current(III/3)

300V

Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Push-in spring connection
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850
Shell color	Black
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	2EDG-PWP-01A(H)
Bridge	/
Marking strip	/
Others	/

Üzleti adatok	
Rendelészám	10030010262
Csomagolási egység	1600
Minimális rendelési mennyiség	
A termékek súlya (csomagolás nélkül)	1.6